VividForms

BBM344

ANIT FOG BACK-LIT BATHROOM MIRROR





DESCRIPTION

This modern LED vanity mirror combines style and practicality with a 5mm copper-free silver surface, three selectable color temperatures (3000K, 4000K, 6000K) in addition to multi-colored LED lights and a convenient touch sensor switch. Its optional anti-fog feature ensures a clear reflection in humid spaces, while the durable aluminum frame and high-quality glass deliver long-lasting performance. With CE-certified components, IP44 moisture resistance, and a CRI of 80+, it offers reliable illumination and a sleek design ideal for both residential and commercial interiors.

APPLICATION

Ideal for residential bathrooms, hotel suites, hospitality spaces, and upscale commercial restrooms where modern design and reliable illumination are desired.

DIMENSIONS

Offered in standard dimensions of 20" x 30", 24" x 36", 30" x 36", 48" x 36", and 60" x 36".

FEATURES

- Color temperature selectable 3000K-4000K-6000K
- Touch sensor switch for easy operation
- Optional anti-fog function for a clear reflection in humid environments.
- IP44-rated with CE-certified LED driver and plug for safety and durability
- Voltage: AC100-240V, 5/60Hz

CONSTRUCTION

The mirror features a durable aluminum frame for strength and corrosion resistance paired with a 5mm copper-free silver glass surface that provides a clear, eco-friendly reflection.

MOUNTING

The mirror supports wall mounting with secure brackets, allowing for stable installation.

WARRANTY

5 year warranty standard, Optional 10 year warranty available upon request.

*IES Files available upon request or visit vivid-forms.com

ORDERING INFORMATION

	Series	Size	Color temperature	Backlight	Anti-Fog	Wire Option

Series	Size	Color Temperature	Backlight	Anti-Fog	Wire Option
BBM 344 Anit Fog Back lit Bathroom Mirror	2030 - 20"X30" 2436 - 24"X36" 3036 - 30"X36" 4836 - 48"X36" 6036 - 60"X36"	3CCT - Color Temp. Selectable 3000K-4000K-6000K	BL - Backlight	AF - Anit-Fog technology and control None - Leave blank for no anit-fog function	HW - Hard-wired leads PL - Plug 100-240VAC



DIMENSION









